


Products in Family

GRSX6275-10/2GB (1 x 2GB 1Rx4 DIMMs)
 GRSX6275-810/2GB (1 x 2GB 2Rx8 DIMMs)
 GRSX6275-10/8GB (1 x 8GB 2Rx4 DIMMs)



Features		Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 30 mm high (1.181" x 5.25") Data Transfer Rate: 10.6 Gigabytes/sec Operating Voltage: 1.5 V ±0.075 Fully RoHS Compliant Thermal Sensor		Each GRSX6275-10 upgrade consists of a single DDR3-1066 Registered ECC DIMM that conforms to JEDEC's DDR3, PC3-8500 standard. One 2K-bit EEPROM is used for Serial Presence Detect and a combination register/PLL with Address and Command Parity is also used. A thermal sensor accurately monitors the DIMM module and can prevent exceeding the maximum operating temperature of 95C.
Dataram Product	Sun Microsystems Product	Supported in these Sun Microsystems systems:
GRSX6275-10/2GB GRSX6275-810/2GB GRSX6275-10/8GB	X4670A Not Offered by Sun Not Offered by Sun	Sun Blade X6275 Server Module

Front view



Notes

Tolerances on all dimensions except where otherwise indicated are \pm 0.13 (.005).

All dimensions are expressed in millimeters [inches]

Back view



Side view

